

# Risk analysis of oil transportation from the Persian Gulf to America in connection with the Suez Canal reconstruction

Larisa Pershina\*, Liudmila Astreina

Admiral Ushakov Maritime State University, Department of Ship Navigation, 93 Lenin's avenue, Novorossisk, 353918, Russia

**Abstract.** The tonnage capacity of the Suez Canal has almost doubled since its reconstruction. The risk analysis of oil and oil products transportation is carried out in the paper, considering this factor from the Persian Gulf to America, and in order to reveal the economic efficiency of the existing recommended routes. According to the research outcomes and calculations, it is proved that the most expensive path is the route through the Suez Canal. It can be profitable on a short haul for transportation to the countries of the Mediterranean Basin and Western Europe due to the low tariff plan for small vessels of the LRI, MR, Handymax, Handysize classes and doubling the freight by reducing the transit time over short distances. An analysis of the probable routes from the Persian Gulf to North America through the Suez Canal and bypassing Africa is carried out in the paper. The economic effect calculation of oil transportation is conducted using the example of the Sea Vigor tanker of the Suezmax class through the Suez Canal and the Cape of Good Hope, considering the distance, the cost of escorting ships through the Suez Canal, the risk assessment and cost of ship security services, the calculation of wind-wave losses of routes bypassing the African continent. Besides, the conclusions and recommendations are formulated in the paper.

## 1 Introduction

Frequently, the key issue in choosing the most rational (optimal) transportation option is the economic effect calculation of all stages of the voyage assignment, starting with the vessel load and the cargo transportation from the unloading berth. The specific conditions of transportation and the voyage tasks determine the efficiency criteria choice. Local (particular) and generalized (complex) efficiency criteria can be distinguished.

If the compared sea routes differ only in one taken indicator, then the local efficiency criteria are applied, excluding the downtime of vessels in the port while waiting for a queue or favorable weather conditions. In this case, the effectiveness of the compared sea routes can be assessed by one indicator: the company's costs of downtime at the points of loading and unloading, or the costs associated with the vessel empty return.

Complex performance indicators are used when the compared routes have several characteristics of the transport process. For instance, such parameters as: deadweight of a vessel, downtime under loading and unloading, specific fuel consumption per route, costs of paying transport tariffs and other charges arising on routes, costs of safety and integrity of cargo, vessel and crew.

In our case, any particular criterion is not enough. We will try to go into the matter applying complex criteria and formulating conclusions.

## 2 Methods and materials

The world oil and gas basins and the role of the Persian Gulf in the world's fuel industry are studied to analyze the routes' efficiency, the main cargo flows of oil from the Persian Gulf are considered. Weather conditions for the selected routes are analyzed. The economic effect of oil transportation is calculated through the Suez Canal and the Cape of Good Hope considering the distance, the cost of navigating ships through the Suez Canal, assessing the risks and cost of ship security services, calculating wind-wave losses of routes to the west and east from the island of Madagascar to the Cape of Good Hope.

## 3 Research results

IEA predicts an increase in oil consumption by 5.4 million barrels per day (up to 96.6 million barrels per day) in 2021, which will restore about 60% of the volume lost as a result of the pandemic.

According to the IEA, in the first quarter of 2021, global demand is not expected to grow; the consumption will decrease by 1 million barrels per day compared to the previous quarter (Table 1). More favorable conditions for the demand development are likely to be established in the second half of the year. In February, global oil production will decline due to Saudi Arabia's policies and the suspension of the USA capacity. OPEC forecasts that the organization members will supply 27.5

\* Corresponding author: [raketki08@mail.ru](mailto:raketki08@mail.ru)


million barrels per day to fully meet demand in 2021. This is about 2 million barrels per day higher than the current production, which gives a chance to weaken the OPEC+ quotas [1].

**Table 1.** World oil production and consumption (mln BBLpd), IEA source [1]

	2020				2021	I quar. 2021 / I quar. 2020, %
	I	II	III	IV	I (forecast)	
<b>Oil production</b>						
OPEC	33.6	30.8	29.2	30.1		
Saudi Arabia	11.8	11.2	10.7	10.9		
USA	18.0	15.9	16.2	16.3	16.5	-8.3
Russia	11.6	10.4	10.1	10.4	10.5	-9.7
World	100.3	92.1	91.1	92.4		
<b>Oil consumption</b>						
China	11.8	14.2	14.7	14.9	14.3	+21.0
Europe (OECD)	13.3	11.0	12.9	12.5	12.3	-7.6
USA	19.7	16.4	18.7	18.8	18.7	-4.9
World	93.8	82.9	92.7	94.7	93.7	-0.1

The OPEC+ agreement looks quite stable, and the start of vaccination programs gives hope for the quarantine restrictions lift, borders opening and, accordingly, a consumption revival. Meanwhile, vaccination is proceeding extremely unevenly in the world and this indicates that comprehensive protection in crucial countries and regions, including the EU, cannot be completed before the summer end, which means that tourism and aviation will remain “on the ground” [1].


Despite the crisis, the dynamics of the growth and decline in oil production/consumption has not practically changed the structure of oil cargo flows (Figure 1). The main oil cargo flows in terms of transportation volume fan out from the Persian Gulf to Asia and Western Europe. Large tankers transport oil to America through African long way, smaller tankers - across the Suez Canal. Other oil cargo flows go from Latin America (Mexico, Venezuela) to the USA and Western Europe.



**Figure 1.** Major oil trade flows of the world in 2019 (mln. tons) [2]


We analyze the considered options for recommended routes along the specified transition areas in the Oceanic Ways of the World when choosing the most profitable route from the Persian Gulf to North America [3], Admiralty Ocean Passages for the World [4].

We carry out the analysis of the selected route options. Consider the features of the route first option through the Strait of Ormuz - to W from the island of Madagascar - Cape of Good Hope - Chesapeake Bay (Figures 2a, 3b, 4a, 4b).




(6.58) ROUTES—Africa ← Aden, Persian Gulf and Karachi.

a) Africa - Aden, Persian Gulf and Karachi;




(6.65) ROUTES—Africa ← Bombay and Colombo.


b) Africa - Bombay and Colombo  
**Figure 2.** Sea routes of the Indian Ocean [4].




(6.63) ROUTES—Aden ←→ Persian Gulf and Karachi.  
 a) Aden - Persian Gulf and Karachi;



b) South Africa - Mozambique Channel and Port Louis  
**Figure 3.** Sea routes of the Indian Ocean [4].



a) West African coast - Cape Palmas, Cape Agulhas and Cape Verde islands;




b) Florida Strait - Europe


**Figure 4.** Sea routes in the Atlantic Ocean [4].

Consider the options for the routes through the Strait of Ormuz - to E from the island of Madagascar - Cape of Good Hope - Chesapeake Bay (Figures 2b, 3b, 4a, 4b).

We analyze the routes through the Strait of Ormuz - Suez Canal - Mediterranean Sea - Strait of Gibraltar - Chesapeake Bay (Figures 3a, 5a, 5b, 4b).



a) East Side



b) West Side

**Figure 5.** Sea routes of the Mediterranean Sea [4].


The short recommendations for calculating the distance obtained as a result of the analysis will be presented in Table 2, and we will show the selected routes in Figure 6 according to the recommendations in



the Oceanic Ways of the World [3], Admiralty Ocean Passages for the World [4] and Ships Routing [5].

**Table 2.** Recommendations and nodal points of routes

No	Brief recommendations for choosing a route	Nodal point coordinates	Source/reference /page
1	Exit from TSS Cape Ras El-Kuh in the Gulf of Oman	25°20' N, 57°20' E	[5] Sh.Rout/B-IV/9
2	The main path goes through point to N from the Comoros. The eastern end of Socotra Island should be left at least 50 miles away.	08°00' N, 52°40' E	[3] No. 9015/ 6.60/74
3	Nodal points along the east coast of Africa and in the Mozambique Channel	11°35' S, 42°50' E 13°35' S, 42°50' E 17°00' S, 40°20' E 26°45' S, 47°45' E	[4] NP 136/ 6/58/69, 6.55/64
4	Nodal points of the route to the east from the island of Madagascar	06°30' N, 60°00' E 14°00' S, 60°00' E 26°45' S, 47°45' E	[4] NP 136/ 6.65/72, 6.58/69, 6.55/64
5	Coast of South Africa. TSS to S Alphonse banks TSS Cape Agulhas	34°45' S, 22°30' E 34°50' S, 21°40' E 34°54' S, 21°20' E 35°05' S, 20°00' E	[5] Sh.Rout/B-IV/14 [5] Sh.Rout/B-IV/13
6	South Side of the Atlantic Ocean: Route from the Cape of Good Hope to Cape Verde Islands	35°05' S, 20°00' E 14°40' N, 24°55' W	[4] NP 136/ 3.42/45
7	Port Said - TSS Strait of Tunis –  TSS Cape Gata	37°10' N, 11°20' E 37°30' N, 09°40' E 36°43' N, 01°53' W 36°36' N, 02°13' W	[4] NP 136/ 5.29/55, 5.30/54 [5] Sh.Rout/B-III/5,6 [5] Sh.Rout/B-III/2
8	TSS Strait of Gibraltar –  TSS Oyo Bank	36°04' N, 05°15' W 35°57' N, 05°55' W 35°57' N, 06°15' W	[5] Sh.Rout/B-III/1 [5] Sh.Rout/B-II/28
9	the Azores	36°40' N, 24°45' W	[4] NP 136/ 2.82/28
10	Entrance to the Chesapeake Bay. TSS at Cape Henry	36°50' N, 75°46' W	[5] Sh.Rout/B-IX/8



**Figure 6.** Selected routes from the Strait of Ormuz to the Chesapeake Bay

The calculation of the distance between the nodal points of the Strait of Ormuz (Bendar Abbas port) - Chesapeake Bay (Norfolk port) is performed in the following ways: by the "BP Marine Distance Tables" electronic program, TMP-2001 (tables of sea distances) and navigation charts for routes bypassing Africa using "Navi Sailor 4000 ECDIS-I" software considering navigation criteria and weather conditions. The obtained calculation results are included in Table 3.

**Table 3.** Distance analysis from Bendar Abbas Port to Norfolk Port

No	Transit option	Departure from Bendar Abbas Port to destination port of Norfolk	Distance, miles		
			«BP Marine Distance Tables»	TMP-2001	Distance difference
1	S <sub>1</sub>	to E from Madagascar	11977	11929	<b>48</b>
2	S <sub>2</sub>	to W from Madagascar	11427	11424	<b>3</b>
3	S <sub>3</sub>	The Suez Canal	8117	7987	<b>130</b>
	S <sub>1</sub> - S <sub>2</sub>	Difference in favor of the path to W from Madagascar	11929 – 11424		<b>505</b>
	S <sub>1</sub> - S <sub>3</sub>	Difference in favor of the path through the Suez Canal	11424 – 7987		<b>3437</b>

The calculation of distances according to "BP Marine Distance Tables" and "Tables of sea distances-2001" showed an insignificant difference in distances according to the existing tables of sea distances - 3 and 50 miles, that is, approximately 3 hours. The difference in the length of the three possible route options provide significant benefits towards 3 route options - through the Suez Canal.

We fill in Table 4 for the analysis of routes excluding IWW, based on the basic technical parameters of the “Sea vigor” tanker of the “Suezmax” class and the calculated data on the routes going from the Strait of Ormuz to the Chesapeake Bay, that is, at  $V_0 = 15$  nodes, deadweight of (t) =158566 and an average fuel consumption of 40 tons per day.

From the data analysis, it follows that under favorable weather conditions, the route through the Suez

**Table 4.** Calculated data for routes from the Strait of Ormuz to the Chesapeake Bay

Route	Distance (miles)	Distance difference	Fuel consumption (t)	Transition time	ETD	ETA	Time difference
to E from Madagascar	11929	-	1047	795.26 h 33 days 3,5 h	015.03.2020 10:00 UTC	017.04.2020 05:30 UTC	-
to W from Madagascar	11424	505	995	761.6 h 31 days 18 h	015.03.2020 10:00 UTC	016.04.2020 10:30 UTC	33.66 h 1 day 9.5 h
Through the Suez Canal	7987	3437	676	532.46 h 22 days 4.5 h	015.03.2020 10:00 UTC	06.04.2020 20:30 UTC	262.8 h 10 days 23 h

The transit cost through the Suez Canal depends on the following factors: vessel's draft, tonnage, height of deck cargo, time of application, timeliness of the vessel's approach, direction, etc. Pilotage fees range from 8 to 12 dollars per tonne with an average cost of over 160,000 dollars per tonne to navigate [6]. The cost for a heavy cargo vessel can reach 1 million dollars or more.

Routes from the Persian Gulf are at increased risk of pirate attacks (Figure 7). According to ship owners, currently, armed guards assist on 50% of vessels crossing the Gulf of Aden and the coast of the Somali Peninsula. Generally, from 3 to 6 guards work on the vessel; they have a complete set of equipment for the job. The guard can earn from 500 to 1000 US dollars per day [8].

Guards board and disembark the vessels in Muscat and Salalah (Oman), Dar es Salaam (Tanzania), Djibouti and Galle (Sri Lanka) [8]. They stay an average of 10-15 days on the vessel; the presence and provision of security services (providing the vessel with passive protection, training the crew on anti-seizure measures, equipping protected premises on the vessel) take about 100,000 dollars for the ship owner [8].

Fuel costs for the route through the Suez Canal will be US \$ 437,710 at a fuel cost of US \$ 647.5 (MGO, Fujairah, AE, [9]).


Thus, based on the averaged data, the operating costs for the Strait of Ormuz - Suez Canal - Chesapeake Bay route (duration 22 days, excluding the time spent on the Suez Canal) will be approximately 1.281.762 US dollars.

Canal is much shorter (11 days) compared to the routes through the Cape of Good Hope bypassing Africa. Accordingly, the costs of these routes are highly dependent on the duration of the voyage and fuel consumption, by about 1/3.

We compare the selected routes by IWW and other economic criteria.

The cost of 31-day and 33-day flights around Africa will be estimated according to the same parameters. The outcomes are tabulated in the summary Table 5 and the difference in calculations is presented in Table 6.

The calculation result has revealed that the most expensive route is through the Suez Canal, while routes to the west and east of the island of Madagascar differ in fuel cost.



**Figure 7.** Borders of pirate zones [7]

**Table 5.** Route efficiency calculation

Route	Distance (miles)	Transition time	Fuel consumption, (t)	Fuel cost (647.5 \$/t)	Vessel security costs, (\$)	Suez transit cost, (\$)	Total expenses, (\$)
to E from Madagascar	11929	795.26 h 33 days 3.5 h	1047	677 932	100 000	-	777 932
to W from Madagascar	11424	761.6 h 31 days 18 h	995	644 252	100 000	-	744 252
Through the Suez Canal	7987	532.46 h 22 days 4.5 h	676	437 710	100 000	744 052	1 281 762

**Table 6.** Route cost difference

Cost difference, (\$) Route	to E from Madagascar	to W from Madagascar	Through the Suez Canal
to E from Madagascar	-	33 680	503 830
to W from Madagascar	33 680	-	537 510
Through the Suez Canal	503 830		-

The calculations were based on  $V_0 = 15$  nodes and did not consider weather conditions. For an accurate comparison of the routes efficiency to W and E from Madagascar, we calculate wind-wave losses on each of them from the Strait of Ormuz to the Cape of Good Hope, where they are further combined into a common route to America.

The universal formula of P.M. Khokhlov is applicable for calculating the loss of vessel speed in

waves. It is possible to clarify the wind-wave losses according to the formulas of V.V. Dremlyug and V.M. Shapaev on specific wind and wave conditions. Yu.I. Tulchinsky formula with a displacement accounting factor of 33,000 to 300,000 tons is suitable taking into account the deadweight of a Suezmax class tanker [10].

The coordinates of the points from the Strait of Ormuz to the Cape of Good Hope were computed using the “Navi Sailor 4000 ECDIS-I” software. The sample of the wave and flow parameters of the routes was performed in separate sections from the English sailing directions of NP 3, 33, 68, and the hydrometeorological map of the Indian Ocean No. 6311 (March) (Table 2).

The program created on the basis of VBA Visual Basic for Applications Excel 2016 was used for speed and accuracy of mathematical calculations [10]. Figures 8 and 9 represent a sample of parameters, Tables 7 and 8 - the outcomes of calculations.

**Table 7.** Calculated parameters for the route to E from Madagascar with flows and excluding them

Course	Calculated parameters					IWW without flow	Calculated parameters		
	S section, miles (NM)	IWW without flow	IWW without flow	IWW without flow	IWW with flow		IWW with flow	IWW with flow	IWW rate with flow
		$\Delta V$ , node	$\Delta t$ , h	$V_0$			$\Delta V$ , node	$\Delta t$ , h	$V_0$
146.1	39.35	-0.07492	-0.01317	14.925	0.5	0.34011	0.05817	15.340	
146.1	15.42	-0.07492	-0.00516	14.925	0.5	0.34005	0.02279	15.340	
140.1	238.40	-0.07121	-0.07581	14.929	0.5	0.31275	0.32460	15.313	
180.0	22.81	-0.09592	-0.00979	14.904	-0.5	-0.09634	-0.00983	14.904	
180.0	2169.66	-0.35399	-3.49601	14.646	-0.5	-0.35421	-3.49818	14.646	
221.9	1029.59	-0.20957	-0.97256	14.790	1.0	-0.15527	-0.71792	14.845	
249.1	1086.44	-0.13254	-0.64570	14.867	1.0	-0.53942	-2.70181	14.461	
240.4	141.49	-0.30425	-0.19529	14.696	1.5	-0.70069	-0.46222	14.299	
262.7	233.92	-0.23300	-0.24605	14.767	1.0	-0.84326	-0.92891	14.157	
262.0	25.45	-0.23524	-0.02703	14.765	1.0	-0.83640	-0.10017	14.164	
242.0	24.36	-0.29943	-0.03308	14.701	1.0	-0.59092	-0.06660	14.409	
	$\Sigma S$ ,miles =5027		$\Sigma IWW$ ,h= -5,7	$V_m=14,8$			$\Sigma IWW$ ,h= -8,1	$V_m=14,7$	
Crossing time	Without flow t,h=339.6 h =14 days 4 h					With flow t,h=341.9 h =14 days 6 h			

**Table 8.** Calculated parameters for the route to W from Madagascar with flows and excluding them

Course	Calculated parameters					IWW without flow	Calculated parameters		
	S section, miles (NM)	IWW without flow	IWW without flow	IWW without flow	IWW with flow		IWW with flow	IWW with flow	IWW rate with flow
		$\Delta V$ , node	$\Delta t$ , h	$V_0$			$\Delta V$ , node	$\Delta t$ , h	$V_0$
146.1	39..30	-0.07492	-0.01315	14.925	0.5	0.34026	0.05812	15.340	
146.1	15.46	-0.07492	-0.00517	14.925	0.5	0.34010	0.02285	15.340	
140.1	238.41	-0.07121	-0.07582	14.929	0.5	0.31271	0.32458	15.313	
180.0	22.94	-0.09592	-0.00984	14.904	-0.5	0.25710	0.02577	15.257	
204.0	632.13	-0.42107	-1.21714	14.579	-1.5	0.97854	2.58079	15.979	
207.7	1634.43	-0.41144	-3.07305	14.589	-1.0	0.54301	3.80670	15.543	
203.1	222.93	-0.27921	-0.28189	14.721	0.5	0.18058	0.17679	15.181	
205.7	133.14	-0.27119	-0.16343	14.729	1.0	0.63011	0.35783	15.630	
209.4	551.10	-0.25931	-0.64632	14.741	1.5	0.14398	0.34929	15.144	
215.5	478.66	-0.38448	-0.83945	14.616	1.5	-0.13464	-0.28903	14.865	
223.4	61.87	-0.35881	-0.10109	14.641	1.5	-0.31480	-0.08842	14.685	
224.5	84.07	-0.35528	-0.13596	14.645	1.5	-0.34059	-0.13021	14.659	
240.4	141.49	-0.30392	-0.19508	14.696	1.5	-0.70037	-0.46200	14.300	
262.7	233.92	-0.23300	-0.24605	14.767	1.0	-0.84326	-0.92891	14.157	
263.3	25.45	-0.23524	-0.02703	14.765	1.0	-0.85376	-0.10240	14.146	
240.8	24.56	-0.29943	-0.03335	14.701	1.0	-0.57051	-0.06474	14.429	
	$\Sigma S$ ,miles=4540		$\Sigma IWW$ ,h= -7,1	$V_m=14,7$			$\Sigma IWW$ ,h= 5,6	$V_m=14,99$	
Crossing time	Without flow t, h=308.8 h =12 days 21 h					With flow t, h=302.9 h =12 days 15 h			



The flow rates on the routes are relatively small (according to hydrometeorological data do not exceed 0.5-1.0 nodes – Tables 7, 8). The flow directions in the sections are both on-coming and passing. The highest flow rate in the Mozambique Channel is up to 1½ nodes,

which makes this crossing section an advantageous not only in time, but also in rate. The gain in time will be approximately 2 days subject to the passing flow in the Mozambique Channel and the current of Cape Agulhas.

**Table 8a: Input and calculation data for route to E from Madagascar**

№	Маршрут			Расчеты																		
	φ	λ	Δ	Расстояние М. Морс	Курс сузы	Курсовой угол волны φ (град.)	Высота Волны H (м)	Скорость течения V <sub>гр</sub>	Направление течения	Игольное расстояние	Скорость сузы	ETA	ВВП без течения ΔV, узл	ВВП с течением Δt, ч	Скорость с ВВП без течения V <sub>с</sub>	ВВП с течением ΔV, узл	ВВП с течением Δt, ч	Скорость с ВВП с течением V <sub>с</sub>				
1	26	21,000	N	56	38,000	E	XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX			
2	25	48,335	N	57	2,490	E	39,35	146,1	34,0	1,0	0,5	180,0	39,35	15,0	15,03.12.15:58	-0,07492	-0,01317	14,925	0,34011	0,05817	15,340	
3	22	32,466	N	59	59,202	E	238,40	140,1	40,0	1,0	0,5	180,0	54,77	15,0	15,03.12.15:59	-0,07492	-0,00516	14,925	0,34005	0,02279	15,340	
4	22	9,656	N	59	59,203	E	228,40	140,1	40,0	1,0	0,5	180,0	293,17	15,0	16,03.12.8:53	-0,07121	-0,07581	14,929	0,31275	0,32460	15,313	
5	14	0,000	S	60	0,000	E	2169,66	180,0	45,0	3,0	-0,5	270,0	2485,64	15,0	22,03.12.11:03	-0,35399	-3,49601	14,646	-0,35421	-3,49818	14,646	
6	26	46,213	S	47	46,376	E	1029,59	221,9	90,0	3,0	1,0	135,0	3515,22	15,0	25,03.12.7:41	-0,20957	-0,97256	14,790	-0,15527	-0,71792	14,845	
7	33	15,000	S	28	15,000	E	1086,44	249,1	114,0	3,0	1,0	135,0	4601,66	15,0	28,03.12.8:07	-0,13254	-0,64570	14,867	-0,53942	-2,70181	14,461	
8	34	25,000	S	25	47,000	E	141,49	240,4	60,5	3,0	1,5	135,0	4743,15	15,0	28,03.12.17:33	-0,30925	-0,19529	14,696	-0,70069	-0,46222	14,299	
9	34	58,552	S	21	5,000	E	233,92	262,7	82,7	3,0	1,0	135,0	4977,07	15,0	29,03.12.10:08	-0,23300	-0,24605	14,767	-0,84326	-0,92891	14,157	
10	34	58,552	S	20	34,268	E	25,45	262,0	82,0	3,0	1,0	135,0	5007,52	15,0	29,03.12.10:50	-0,23524	-0,02703	14,765	-0,83640	-0,10017	14,164	
15	В	35	10,000	S	20	8,000	E	24,36	242,0	62,0	3,0	1,0	135,0	5026,88	15,0	29,03.12.12:28	-0,29943	-0,03308	14,701	-0,59092	-0,06660	14,409

a) on the route to E from Madagascar

**Table 8b: Input and calculation data for route to W from Madagascar**

№	Маршрут			Расчеты																	
	φ	λ	Δ	Расстояние М. Морс	Курс сузы	Курсовой угол волны φ (град.)	Высота Волны H (м)	Скорость течения V <sub>гр</sub>	Направление течения	Игольное расстояние	Скорость сузы	ETA	ВВП без течения ΔV, узл	ВВП с течением Δt, ч	Скорость с ВВП без течения V <sub>с</sub>	ВВП с течением ΔV, узл	ВВП с течением Δt, ч	Скорость с ВВП с течением V <sub>с</sub>			
1	26	21,000	N	56	38,000	E	XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX	XXXXXX		
2	25	48,365	N	57	2,379	E	39,30	146,1	34,0	1,0	0,5	180,0	39,30	15,0	15,03.12.16:20	-0,07492	-0,01315	14,925	0,34026	0,05812	15,340
3	22	32,470	N	59	59,200	E	238,41	140,1	40,0	1,0	0,5	180,0	293,17	15,0	16,03.12.9:15	-0,07121	-0,07582	14,929	0,31271	0,32458	15,313
4	22	9,534	N	59	59,208	E	22,94	180,0	0,0	1,0	-0,5	45,0	316,11	15,0	16,03.12.10:47	-0,09992	-0,00984	14,904	0,25710	0,02577	15,257
5	12	32,000	N	55	30,000	E	632,13	204,0	24,1	3,0	-1,5	45,0	948,23	15,0	18,03.12.4:55	-0,42107	-1,21714	14,579	0,97884	2,58079	15,979
6	11	35,000	S	42	50,000	E	1694,43	207,7	27,1	3,0	-1,0	45,0	2802,66	15,0	22,03.12.7:53	-0,41144	-0,07305	14,589	0,94901	3,86970	15,543
7	15	0,000	S	41	20,000	E	222,93	203,1	68,3	3,0	0,5	180,0	2805,59	15,0	23,03.12.8:45	-0,27921	-0,28189	14,721	0,18058	0,17679	15,181
8	17	0,000	S	40	20,000	E	133,14	205,7	70,8	3,0	1,0	180,0	2938,73	15,0	23,03.12.17:37	-0,27119	-0,16343	14,729	0,63011	0,35783	15,630
9	25	0,000	S	35	30,000	E	551,10	209,4	74,5	3,0	1,5	135,0	3489,83	15,0	25,03.12.6:22	-0,25931	-0,64632	14,741	0,14398	0,34929	15,144
10	31	30,000	S	30	15,000	E	478,66	215,5	35,5	3,0	1,5	135,0	3968,49	15,0	26,03.12.14:16	-0,38448	-0,83945	14,616	-0,13464	-0,28901	14,865
11	32	15,000	S	29	25,000	E	61,87	223,4	43,5	3,0	1,5	135,0	4030,37	15,0	26,03.12.18:24	-0,35881	-0,10109	14,641	-0,31480	-0,08842	14,685
12	33	15,000	S	28	15,000	E	84,07	224,5	44,6	3,0	1,5	135,0	4114,44	15,0	27,03.12.0:00	-0,35528	-0,13996	14,645	-0,34089	-0,13021	14,659
13	34	25,000	S	25	47,000	E	141,49	240,4	60,6	3,0	1,5	135,0	4255,92	15,0	27,03.12.9:26	-0,30392	-0,19508	14,696	-0,70037	-0,46300	14,200
14	34	53,000	S	21	5,000	E	233,92	262,7	82,7	3,0	1,0	135,0	4489,85	15,0	28,03.12.10:02	-0,23300	-0,24605	14,767	-0,84326	-0,92891	14,157
15	34	58,000	S	20	34,175	E	25,45	263,3	82,0	3,0	1,0	135,0	4515,30	15,0	28,03.12.2:44	-0,23524	-0,02703	14,765	-0,85376	-0,10240	14,146
В	35	10,000	S	20	8,000	E	24,56	240,8	62,0	3,0	1,0	135,0	4539,86	15,0	28,03.12.4:22	-0,29943	-0,03335	14,701	-0,57051	-0,06474	14,429

b) on the route to W from Madagascar

Figure 8. Table of input and calculation data





Figure 9. Comparison diagrams of wind-wave losses without regard to flows and with them:

The variation range of wind and wave losses is insignificant - 0.1-0.2 nods on each route. The gain in time arises only on certain sections of the route, which, according to Student's theory, do not differ significantly despite the disagreements (Diagrams - Figure 9), and are practically homogeneous (Wilcoxon test).

## 4 Conclusion

The research outcome has proven that the shortest timing route is the most expensive one (Figure 10). It can be profitable on a short haul for transportation to the countries of the Mediterranean Basin and Western Europe on vessels of the LRI, MR, Handymax, Handysize classes reducing the amount of road charge through the Suez due to tonnage. At the same time, it is feasible to perform two or three voyages per month, and, accordingly, get an income for freight two to three times more.



**Figure 10.** Efficiency diagram of routes from the Strait of Ormuz to the Chesapeake Bay, %

The Suez Canal Administration is going for significant discounts during a pandemic and a global decline in fuel prices, especially for long-distance routes to America and the Caribbean and for large vessels of the VLCC class. Such concessions ensure the flow of large-tonnage vessels through the Suez Canal, since the canal capacity after reconstruction doubles up to 5.8 million tons per day. Moreover, the number of vessels increased by a third - from 45-60 to 75 vessels in both directions [6].

Meanwhile, tankers of the VLCC and Suezmax class prefer to use longer routes (11 days) bypassing Africa, because the total cost of cargo delivery is about 40% less.

If one chooses between the route to the west or east of Madagascar in accordance with the hydrometeorological data for March, today the western route along the African coast is more profitable for a number of reasons. Firstly, the crossing time is 31-39 hours shorter, depending on the flow. Secondly, the difference in wind-wave losses is minor - 0.1-0.2 nodes, and due to the flow, is reduced to zero. Thirdly, the route has become less dangerous compared to 2014-2018 with respect to the vessels escort under protection and a decrease in the risk of pirate attacks.

Routes to the east of Madagascar passes through the "open sea", bypassing pirate-hazardous areas from the archipelagos and the coastal zone, and the routes are safer depending on seasonal conditions (tropical cyclones).

In conclusion, the reasons that form the main traffic of oil and oil products in the Indian Ocean can be singled out:

- presence of deposits in the Arabian Peninsula and the Persian Gulf;
- direction of transportation: to Asia, Europe or America;
- vessel tonnage and voyage assignment;
- voyage duration and costs of fuel, wages, downtime, etc.;
- road charges arising from the passage of limiting sections;
- hydrometeorological conditions at the route time ensuring safe vessel pilotage;
- risk assessment of piracy on the route and the resulting inevitable costs of ship owners for vessel security and insurance of the crew, vessel, cargo;
- socioeconomic conditions, sometimes dramatically changing the market conditions and even the well-established seasonal routes of the World ocean.

## References

1. *Energy Bulletin*. **93**, 2-8, (2021) Available at: [https://ac.gov.ru/uploads/2-Publications/energo/energo\\_dec\\_2020.pdf](https://ac.gov.ru/uploads/2-Publications/energo/energo_dec_2020.pdf)
2. *BP Statistical Review of World Energy*. Available at: <https://www.bp.com/content/dam/bp/business-sites/en/global/corporate/pdfs/energy-economics/statistical-review/bp-stats-review-2020-full-report.pdf>
3. *Ocean paths of the world 9015* (Main Directorate of Navigation and Oceanography of the Ministry of Defense, 1980)
4. *Admiralty Ocean Passages for the World* (United Kingdom Hydrographic Office, 2004).
5. *Ships' Routing*. (IMO, 2015).
6. *Road charge calculator*. Available at: <https://www.suezcanal.gov.eg/English/Navigation/Tolls/Pages/TollsTable.aspx>.
7. L. Astreina, L. Pershina. *Operation of marine transport*, **4** (85), 68-74. Available at: [https://aumsu.ru/images/sbornik/vypuski/emt\\_4\\_2017.pdf](https://aumsu.ru/images/sbornik/vypuski/emt_4_2017.pdf)



8. *Navy*. 2012. **5**. Available at: <http://www.morvesti.ru/themes/1700/53367/>
9. World bunker prices. Available at: <http://www.mabux.ru/bunkerprices/index.jsp>.
10. L. Pershina. *Operation of marine transport*, **2 (87)**, PP. 58-66. Available at: [https://aumsu.ru/images/sbornik/vypuski/\\_2\\_2018.pdf](https://aumsu.ru/images/sbornik/vypuski/_2_2018.pdf)